GROOVED REDUCING COUPLINGS
Model 105



The ARGCO Model 105 reducing coupling allows for direct reduction on a piping run and eliminates the need for a concentric reducer and couplings. The specially designed rubber gasket helps prevent small pipe from telescoping into larger pipe during vertical assembly.

Caution: Model 105 couplings should not be used with an end cap, as the end may be sucked into the pipe when draining the system.

Pipe Material
- Carbon steel, Schedule 10, Schedule 40.
  For use with alternative materials and wall thicknesses please contact ARGCO.

Maximum Working Pressure
- Up to 300 psi/2517 kPa.

Function
- Joins carbon steel pipe.
- Provides a rigid pipe joint designed to restrict axial or angular movement.

CERTIFICATIONS/LISTINGS
Underwriters Laboratories, Underwriters Laboratories Canada, Factory Mutual.

SPECIFICATIONS - MATERIAL
Housing Sections: Ductile Iron conforming to ASTM A 536, Grade 65-45-12.

Housing Coating:
Standard: Orange Enamel
Available: Hot Dipped Galvanized

Gasket:
Standard: Grade E EPDM (Type A)
ARGCO's products are listed by Underwriters Laboratories UL Canada and Approved by Factory Mutual for we and dry (oil free air) sprinkler services within the rated working pressure.

Bolts and Nuts
Standard: Carbon Steel oval neck track bolts meeing ASTM A449 and ISO 898-1. Carbon steel hex nuts meet ASTM A563 Grade B.
Nuts and Bolts are zinc electroplated per ASTM B633 NZ/FE5, finish Type III.
Available: Stainless Steel. Meets ASTM F593, Group 2 (316 stainless steel), condition CW.
Hex nuts meets ASTM F594, Group 2 (316 stainless steel), condition CW, with galling-resistant coating.

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	

GROOVED REDUCING COUPLINGS

Model 105



ARGCO Grooved Couplings are suitable for fire protection systems, water supply systems, and other process systems of higher working pressure.

						Deflection		Dimensions			
Item #	Nominal Size in/mm	Actual O.D. in/mm	Max.Working Pressure psi/Bar	Max. End Load Lbs/KN	Axial Displacement in/mm	Degree Per Coupling (°)	Pipe in/ft mm/m	A inches mm	B inches mm	C inches mm	Bolt Size inches mm
7010109	1-1/2 x1-1/4	1.9 x 1.669	300	852	0.0625	1° - 54'	33	2.76	4.45	1.77	3/8 x 2
	40 x 32	48.3 x 42.4	20	3.79	1.6	1° - 54'	0.4	70	113	45	M10 x 50
7010110	2 x 1-1/4	2.375 x 1.669	300		0.0625						3/8 x 2
	50 x 32	60.3 x 42.4	20		1.6						M10 x 50
7010111	2 x 1-1/2	2.375 x 1.9	300	1327	0.0625	1° - 31'	27	3.23	5.12	1.81	3/8 x 2-1/8
	50 x 40	60.3 x 48.3	20	5.91	1.6	1° - 31'	0.32	82	130	46	M10 x 50
7010112	2-1/2 x 2	2.875 x 2.375	300	1945	0.0625	1° - 15'	22	3.82	5.94	1.81	3/8 x 2-1/8
	65 x 50	73 x 60.3	20	8.66	1.6	1° - 15'	0.26	97	151	46	M10 x 50
7010113	3 x 2	3.5 x 2.375	300	2885	0.0625	1° - 02'	18	4.41	6.56	1.81	1/2 x 2-5/8
	80 x 50	88.9 x 60.3	20	12.84	1.6	1° - 02'	0.22	112	166.6	46	M12 x 65
7010114	3 x 2-1/2	3.5 x 2.875	300	2885	0.0625	1° - 02'	18	4.41	6.56	1.81	1/2 x 2-5/8
	80 x 65	88.9 x 73.0	20	12.84	1.6	1° - 02'	0.22	112	166.6	46	M12 x 65
7010115	4 x 2	4.5 x 2.375	300	4769	0.125	1° - 36'	28	5.55	7.87	1.97	1/2 x 2-5/8
	100 x 50	114.3 x 2.375	20	21.22	3.2	1° - 36'	0.34	141	200	50	M12 x 65
7010116	4 x 2-1/2	4.5 x 2.875	300	4769	0.125	1° - 36'	28	5.55	7.87	1.97	1/2 x 2-5/8
	100 x 65	114.3 x 73.0	20	21.22	3.2	1° - 36'	0.34	141	200	50	M12 x 65
7010117	4 x 3	4.5 x 3.5	300	4769	0.125	1° - 36'	28	5.58	7.87	1.97	1/2 x 2-5/8
	100 x 80	114.3 x 88.9	20	21.22	3.2	1° - 36'	0.34	141.8	200	50	M12 x 65
7010118	5 x 4	5.56 x 4.5	300	7124	0.125	1° - 18'	23	6.65	9.25	2.05	5/8 x 3-1/8
	125 x 100	139.7 x 114.3	20	31.70	3.2	1° - 18'	0.27	169	235	52	M16 x 80
7010119	6 x 4	6.625 x 4.5	300	9950	0.125	1° - 07'	20	7.76	10.83	2.05	5/8 x 3-1/8
	150 x 100	165.1 x 114.3	20	44.27	3.2	1° - 07'	0.24	197	275	52	M16 x 80
7010120	8 x 6	8.625 x 6.625	300	17524	0.125	1° - 50'	15	10.08	13.23	2.28	3/4 x 4-1/3
	200 x 150	219.1 x 168.3	20	77.97	3.2	1° - 50'	0.18	256	336	58	M20 x 110

- Deflection or angular movement is the maximum value that a coupling allows under no internal pressure.
- Working Pressure and End Load are total, from all internal and external loads, based on standard weight (ANSI) steel pipe, standard roll or cut grooved in accordance with ARGCO specifications.
- The allowable pipe separation dimension shown is for system layout purposes only. ARGCO couplings are considere rigid connections and will not accommodate expansion or contraction of the piping system.

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	