GROOVED STANDARD RADIUS CROSS

Model 401



Available Sizes
• 2" through 12" (50 through 300 mm)

Pipe Material
• Carbon steel, Schedule 10, Schedule 40.
For use with alternative materials and wall thicknesses please contact ARGCO.

Maximum Working Pressure
• Up to 300 psi/20 bar

Function
• Joins carbon steel pipe.
• Provides a rigid pipe joint designed to restrict axial or angular movement.

CERTIFICATIONS/LISTINGS
Underwriters Laboratories, Underwriters Laboratories Canada, Factory Mutual.

			Model 401 Cross	
Nominal Size in/mm	Pipe O.D. in/mm	Max Working Pressure psi/Bar	Item #	C-E inches mm
1-1/4"	1.669	300	7010230	---
32	42.4	20		---
1-1/2"	1.9	300	7010231	---
40	48.3	20		---
3"	3.5	300	7010234	3.39
80	88.9	20		86
10"	10.75	300	7010239	8.46
250	273	20		215

SPECIFICATIONS - MATERIAL
Housing Sections: Ductile Iron conforming to ASTM A 536, Grade 65-45-12.

Housing Coating:
Standard: Orange Enamel
Available: Hot Dipped Galvanized

• Working Pressure and End Load are total, from all internal and external loads, based on standard weight (ANSI) steel pipe, standard roll or cut grooved in accordance with ARGCO specifications.

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	